



Baltic Treasures

BY TRAVERSE WOOD

PRODUCT DATA SHEET

Application: Floors + Walls + Ceilings

Type: Engineered Wood Flooring

Species: European White Oak

Grade: European Nature & Classic Grade with filled knots

Size: Total Thickness 5/8 x 5.5" Width x 22.83" Length

Wear Layer: 3/16 " (4mm) Solid European White Oak

Base Layer: 1/2" (9 mm) ply Baltic Birch

Cut: Plain Sawn

Finish: Bona UV Lacquer Finish

Janka Scale Rating: 1360

Fire/Smoke: N/A

Performance: Radiant Heating: YES

Installation Method: Nailed, Glued or Floated

Installation Area: On Grade, Above Grade, Below Grade

Matching Trims: YES

Warranty: 5 Years Commercial / 25 Years Residential

Recommended Adhesives: Divergent TimberRigid AF: Premium Urethane
Divergent TimberTight AF: Premium Urethane, 100% RH barrier, sound control

Any covering should be taped, using a low-adhesion tape, to base or shoe mouldings. Do not tape to finished flooring. When taping paper or sheets together, tape them to each other, not to the floor.

Follow NWFA Standards

As a general rule for solid and engineered wood flooring, with geographic exceptions, appropriate temperature and humidity conditions are defined as those conditions where the interior environment is controlled to stay within a relative humidity range between 30% and 50% and a temperature range between 60-80 degrees Fahrenheit. These ranges are likely to be the average of all types of wood products used in normal environments assuming common heating and cooling equipment is used to ensure human comfort.