



# Baltic Treasures

BY TRAVERSE WOOD

## PRODUCT DATA SHEET

**Application:** Floors + Walls + Ceilings

**Type:** Engineered Wood Flooring

**Species:** European White Oak

**Grade:** European Nature & Classic Grade with filled knots

**Size:** Total Thickness 5/8 x 7" Width x 86.61" Length

**Wear Layer:** 3/16" (4mm) Solid European White Oak

**Base Layer:** 1/2" (12 mm) ply Baltic Birch

**Cut:** Plain Sawn

**Finish:** Bona UV Lacquer Finish

**Janka Scale Rating:** 1360

**Fire/Smoke:** N/A

**Performance: Radiant Heating:** YES

**Installation Method:** Nailed, Glued or Floated

**Installation Area:** On Grade, Above Grade, Below Grade

**Matching Trims:** YES

**Warranty:** 5 Years Commercial / 25 Years Residential

**Recommended Adhesives:** Divergent TimberRigid AF: Premium Urethane  
Divergent TimberTight AF: Premium Urethane, 100% RH barrier, sound control

Any covering should be taped, using a low-adhesion tape, to base or shoe mouldings. Do not tape to finished flooring. When taping paper or sheets together, tape them to each other, not to the floor.

## Follow NWFA Standards

As a general rule for solid and engineered wood flooring, with geographic exceptions, appropriate temperature and humidity conditions are defined as those conditions where the interior environment is controlled to stay within a relative humidity range between 30% and 50% and a temperature range between 60-80 degrees Fahrenheit. These ranges are likely to be the average of all types of wood products used in normal environments assuming common heating and cooling equipment is used to ensure human comfort.